





























5 Connecting cables

Part reference ¹⁾	Size	Number of poles	For N.O. / N.C.	Type / Cable	Output	LED ²⁾	Execution	
S08-3FVG-020	S8	3	N.O. / N.C.	type 4 / PVC 2 m	-	-	A	
S08-3FUG-020	S8	3	N.O. / N.C.	type 14 / PUR 2 m	-	-	A	
S08-3FVW-020	S8	3	N.O. / N.C.	type 4 / PVC 2 m	-	-	B	
S08-3FUW-020	S8	3	N.O. / N.C.	type 14 / PUR 2 m	-	-	B	
S08-3FUW-020-904	S8	3	N.O. / N.C.	type 6 / PUR 2 m	NPN	yellow / green	C	
S08-3FUW-020-905	S8	3	N.O. / N.C.	type 6 / PUR 2 m	PNP	yellow / green	D	
S08-4FVG-020	S8	4	N.O. / N.C.	type 4 / PVC 2 m	-	-	E	
S08-4FUG-020	S8	4	N.O. / N.C.	type 14 / PUR 2 m	-	-	E	
S08-4FVW-020	S8	4	N.O. / N.C.	type 4 / PVC 2 m	-	-	F	
S08-4FUW-020	S8	4	N.O. / N.C.	type 14 / PUR 2 m	-	-	F	
S12-3FVG-020	S12	3	N.O.	type 9 / PVC 2 m	-	-	G	
S12-3FUG-020	S12	3	N.O.	type 11 / PUR 2 m	-	-	G	
S12-3FVW-020	S12	3	N.O.	type 9 / PVC 2 m	-	-	H	
S12-3FUW-020	S12	3	N.O.	type 11 / PUR 2 m	-	-	H	
S12-3FUW-020-904	S12	3	N.O.	type 10 / PUR 2 m	NPN	yellow / green	I	
S12-3FUW-020-905	S12	3	N.O.	type 10 / PUR 2 m	PNP	yellow / green	J	
S12-3FVG-020-015	S12	3	N.O. / N.C.	type 8 / PVC 2 m	-	-	K	
S12-3FUG-020-015	S12	3	N.O. / N.C.	type 11 / PUR 2 m	-	-	K	
S12-3FVW-020-015	S12	3	N.O. / N.C.	type 8 / PVC 2 m	-	-	L	
S12-3FUW-020-015	S12	3	N.O. / N.C.	type 11 / PUR 2 m	-	-	L	
S12-4FVG-020	S12	4	N.O. / N.C.	type 9 / PVC 2 m	-	-	M	
S12-4FUG-020	S12	4	N.O. / N.C.	type 11 / PUR 2 m	-	-	M	
S12-4FVW-020	S12	4	N.O. / N.C.	type 9 / PVC 2 m	-	-	N	
S12-4FUW-020	S12	4	N.O. / N.C.	type 11 / PUR 2 m	-	-	N	
S12-5FVG-020	S12	5	N.O. / N.C.	type 4 / PVC 2 m	-	-	O	
S12-5FUG-020	S12	5	N.O. / N.C.	type 7 / PUR 2 m	-	-	O	
S12-5FVW-020	S12	5	N.O. / N.C.	type 4 / PVC 2 m	-	-	P	
S12-5FUW-020	S12	5	N.O. / N.C.	type 7 / PUR 2 m	-	-	P	

¹⁾ **bold:** preferred types

²⁾ LED yellow: switching state / green: supply voltage

Specifications

	Section	Conductor	Sleeve material	Wire insulation
Type 1	0.055 mm ²	30 x 0.05 mm Ø	PUR	PVC
Type 2	0.14 mm ²	18 x 0.10 mm Ø	PVC	PVC
Type 3	0.14 mm ²	72 x 0.05 mm Ø	PUR	PVC
Type 4	0.25 mm ²	32 x 0.10 mm Ø	PVC	PVC
Type 5	0.25 mm ²	19 x 0.13 mm Ø	PUR	PVC
Type 6	0.25 mm ²	67 x 0.07 mm Ø	PUR	PVC
Type 7	0.25 mm ²	128 x 0.05 mm Ø	PUR	PVC
Type 8	0.34 mm ²	7 x 0.25 mm Ø	PVC	PVC
Type 9	0.34 mm ²	42 x 0.10 mm Ø	PVC	PVC
Type 10	0.34 mm ²	88 x 0.07 mm Ø	PUR	PVC
Type 11	0.34 mm ²	180 x 0.05 mm Ø	PUR	PVC
Type 12	0.25 mm ²	128 x 0.05 mm Ø	PVC	PVC
Type 13	0.34 mm ²	180 x 0.05 mm Ø	TPE-S	TPE-S
Type 14	0.25 mm ²	32 x 0.10 mm Ø	PUR	PVC

